





System Specification	WorkCentre 3335	WorkCentre 3345
One-Sided Speed		
8.5 x 11 in.	Up to 35 ppm	Up to 42 ppm
A4 / 210 x 297 mm	Up to 33 ppm	Up to 40 ppm
8.5 x 14 in. / 216 x 356 mm	Up to 28 ppm	Up to 34 ppm
Two-Sided Speed		
8.5 x 11 in.	Up to 17 ppm	Up to 21 ppm
A4 / 210 x 297 mm	Up to 16 ppm	Up to 20 ppm
8.5 x 14 in. / 216 x 356 mm	Up to 14 ppm	Up to 17 ppm
Monthly Duty Cycle <sup>1</sup>	Up to 50,000 pages / month	Up to 80,000 pages / month
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 4,000 pages	Up to 6,000 pages
Processor	1 GHz	
Memory	1.5 GB	
Connectivity	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi	
Paper Handling	WorkCentre 3335	WorkCentre 3345
Document Feeder		
Capacity <sup>3</sup>	Automatic Document Feeder (ADF): 50 sheets	Reversing Automatic Document Feeder (RADF): 50 sheets
Sizes	Custom Sizes: 5.6 x 5.8 in. to 8.5 x 14 in. / 142 x 148 mm to 216 x 356 m	nm
Weights	16 lb. to 28 lb. bond / 60 to 105 gsm	12.5 lb. to 28 lb. bond / 50 to 105 gsm
Bypass Tray		
Capacity <sup>3</sup>	50 sheets	50 sheets
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm	
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm	
Media Types	Archive Bond Card Stock Custom Envelopes Heavyweight Labels Lightweight Plain Preprinted Recycled Transparencies	
Tray 1		
<b>Capacity</b> <sup>3</sup>	250 sheets	
Sizes	Custom Sizes 3.9 x 5.8 in. to 8.5 x 14 in. / 99 x 147 mm to 216 x 356 mm	
Weights	16 lb. bond to 43 lb. bond / 60 to 163 gsm	

Tray 1	2 3333/3343 Multifuliction Printer		
-	Archive		
Media Types	Bond		
	Card Stock Heavyweight		
	Lightweight Plain		
	Recycled		
Additional Tray			
Capacity <sup>3</sup>	550 sheets		
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm		
Weights	16 lb. to 43 lb. bond / 60 to 163 gsm		
Media Types	Archive		
	Bond Card Stock		
	Heavyweight		
	Lightweight Plain		
	Recycled		
Total Capacity			
Device Standard Capacity <sup>3</sup>	300 sheets		
Device Total Capacity <sup>3</sup>	850 sheets		
Paper Output			
Output Capacity <sup>3</sup>	150 sheets		
Automatic 2-Sided	Standard	Standard	
Device Specification	WorkCentre 3335	WorkCentre 3345	
Electrical Requirements			
North America	110-127 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 7A		
Europe	220-240 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 5A		
Power Consumption			
Operation <sup>4</sup>	Maximum 700 watts		
Standby Mode <sup>4</sup>	Maximum 50 watts		
Power Off Mode <sup>4</sup>	Maximum 0.1 watts		
Sleep Mode <sup>4</sup>	Maximum 3.5 watts		
Warm-up (from Sleep Mode)	As fast as 35 seconds		
Operating Environment			
Required Temperature Range			
Storage	32°F to 104°F / 0°C to 40°C		
Operating	50°F to 90°F / 10°C to 32°C		
Required Reletive Humidity	20% to 80%		
Sound Power Levels			
Operating	55 dB(A) or less	57 dB(A) or less	
Standby	26 dB(A) or less	26 dB(A) or less	
Sound Pressure Levels Operating	55 dB(A) or less	57 dB(A) or less	
Standby	26 dB(A) or less	26 dB(A) or less	
Dimensions and Weight (unpacka			
WorkCentre 3335			
Worked SSSS	Depth: 16.6 in. / 420.6 mm		
	Height: 17.7 in. / 449 mm		
	Weight: 34.19 lb. / 15.51 kg		
WorkCentre 3345	Width: 18.5 in. / 469 mm		
	Depth: 17.5 in. / 444.3 mm Height: 19 in. / 482.6 mm		
	Weight: 38.07 lb. / 17.27 kg		
	I .		

Dimensions and Weight (unpackaged)		
550-sheet Paper Tray	Width: 14.4 in. / 366 mm Depth: 17.9 in. / 454 mm Height: 5.7 in. / 146 mm Weight: 11.82 lb. / 5.36 kg	
Dimensions and Weight (packaged	d)	
WorkCentre 3335	Width: 21 in. / 533 mm Depth: 21.6 in. / 549 mm Height: 23.6 in. / 600 mm Weight: 46.5 lb. / 19.26 kg	
WorkCentre 3345	Width: 23.1 in. / 588 mm Depth: 21.6 in. / 549 mm Height: 24.6 in. / 626 mm Weight: 47.1 lb. / 21.4 kg	
550-sheet Paper Tray	Width: 22.2 in. / 563 mm Depth: 19.6 in. / 497 mm Height: 11.2 in. / 285 mm Weight: 16.8 lb. / 7.62 kg	
System Certification/Regulatory C	ompliance	
Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition Section 508 NOM GS Mark EAC ROHS Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix™ Certified Cerner (undergoing evaluation) Apple® AirPrint® 1.5 certification Google Cloud Print™ (device is compliant/tested, but has not been formerly certified) Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.	
Сору	WorkCentre 3335	WorkCentre 3345
Document Scanner	Automatic Document Feeder with 50-sheet capacity	Reversing Automatic Document Feeder with 50-sheet capacity
Document Scanner Size	Platen: Up to 8.5 x 11.7 in / A4 ADF: 8.5 x 14 in. / 216 x 356 mm	Platen: Up to 8.5 x 11.7 in / A4 RADF: 8.5 x 14 in. / 216 x 356 mm
Simplex Speed	Up to 30 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	Up to 40 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm
Duplex Speed	Up to 12 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	Up to 8.4 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm
First-Copy-Out Time	As fast as 13 seconds from the Platen	
Sides (input:output)	1:1 and 1:2	1:1, 1:2, 2:2, and 2:1
Quantity	1 to 999	
Resolution	Up to 600 x 600 dpi	
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments	
Concurrency	Concurrent scanning and printing	
Copy Features	Automatic Background Suppression Darkness Control ID Card Copy Margin Shift N-up Job Build Photo Mode Programme Ahead Booklet Creation Book Copying with Centre Erase Edge Erase Job Interrupt Poster Copying	

Print	WorkCentre 3335	WorkCentre 3345
First-Page-Out Time	As fast as 6.5 seconds <sup>5</sup>	
Resolution	Up to 1200 x 1200 dpi image quality	
Page Description Languages	PostScript 3 compatible PCL® 5e, 6 PDF Direct TIFF JPEG	
Maximum Print Area	4 mm edge of paper	
Print Features	Watermarks Collation Automatic Two-sided Printing N-up Poster Printing Booklet Print Custom Page Size Fit to Page Scaling Draft Mode Earth Smart Printing Print from USB Job Scheduling Print from Local Drive Save Save and Print	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL	
Operating Systems	Microsoft® Windows® Vista and later Mac OS® 10.8.x and later Various Linux® and Unix distributions	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD  NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)  AppleTalk®: EtherTalk®  Microsoft Windows Networking over IP  Bonjour® / Airprint®  IPv6  Secure FTP  Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MI	DNS, SSDP
Font Capability	136 PostScript fonts 111 scalable PCL fonts 1 Bitmap PCL font	
Mobile Solutions and Mobile Device	te Apps	
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device. 6	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
Scan	WorkCentre 3335	WorkCentre 3345
Capability	Colour and Black-and-white	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is	,
Input Speed - Black and White	Scan up to 20 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	Scan up to 24 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm
Input Speed - Colour Resolution	Scan up to 6 ipm — 8.5 x 11 in. / A4 / 210 x 297 mm  Black and White: Optical — 600 x 600 dpi Enhanced up to 4800 x 4800 dpi	Scan up to 8 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm
Bit Depth	8-bit Greyscale	
- = =p==:		

Scan	WorkCentre 3335	WorkCentre 3345
Maximum Scan Area	Platen: Up to 8.5 x 11 in. / A4	
Muximum Scun Area	Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm	
Network Filing Protocol	FTP SMB/SMB2 SMTP/POP3	
File Formats	PDF Single-page and Multi-page TIFF JPEG BMP	
Scan Driver Compatibility	WIA TWAIN	
Supported Scan Destinations	Scan to Email (SMTP/POP3) Scan to WSD Scan to Application (TWAIN Network) Scan to WSD (WSD Scan) Scan to Mac 10.9 or later (Network/Mac ICA) Scan to USB Scan to Network Computer (SMB/FTP) Scan to Folder	
Security	WorkCentre 3335	WorkCentre 3345
Security Features	802.1x Secure HTTPS (SSL/TLS) Secure IPP Secure Print SSL IP Filtering IPv6 SNMP v3 WEP (64-/128-bit) WPA2-PSK (AES) WPA / WPA2-Personal WPA / WPA2-Enterprise Network Address Book Authentication (LDAP, Windows Kerberos)	
WiFi Security		
	Authentication Method	Encryption
	Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2™ Enterprise WPA Enterprise Authentication Method options: • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TLS PAP • EAP-TTLS CHAP	WEP 64 / 128-bit ASCII / HEX TKIP AES TKIP AES
Fax <sup>7</sup>	WorkCentre 3335	WorkCentre 3345
Fax Speed	33 Kbps	
Memory	5 MB	50 MB
Resolution	Standard: Black and White: 203 x 98 dpi / Colour: 200 x 200 dpi (TX only) Fine: Black and White: 203 x 196 dpi / Colour: 200 x 200 dpi (TX only) Super Fine: Black and White: 600 x 600 dpi / Colour: 200 x 200 dpi (TX only)	
Compression	MH/MR/MMR/JBIG/JPEG	
Fax Features	Address Book (Up to 200 speed dials, 209 group dials) Auto Redial Auto Reduction Colour Fax Send Delayed Send Fax Forward to Email/Fax Junk fax Protection Memory Receive PC Fax (Windows only) Secure Fax	
Device Management		
Xerox <sup>®</sup> CentreWare <sup>®</sup> Web		
Device Status	Web server embedded  • Tray status/contents  • Consumables status	
Print Queue Viewing	Complete job print queue management—hold, release, promote and de	elete

Aerox WorkCerit	re® 3335/3345 Multifunction Pr	inter	
Device Management			
Xerox® CentreWare® Web			
Job Submission	Print-ready files (PS, PCL®5c/6, PDF, TIFF Output feature selection		
Device Administration	Allows simple, remote installation setting of configuration options and $\boldsymbol{r}$	nanagement of the device.	
Browsers	Microsoft® Internet Explorer 6, 7 Firefox® 2., 3 Safari® 3.0		
Xerox <sup>®</sup> CentreWare <sup>®</sup> Internet Service	ces – Integrated Device Web Page		
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> </ul>		
Xerox® Standard Accounting (Stand	dard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>		
Remote Print Services			
Xerox <sup>®</sup> MeterAssistαnt <sup>®</sup> Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consumingend-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox® SuppliesAssistant® Service	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.		
What's In The Box			
	WorkCentre 3335 Multifunction Printer or WorkCentre 3345 Multifunction Printer  Standard Capacity Print cartridge: 2,600 pages <sup>5</sup> Software and Documentation CD (with Safety, Regulatory, Recycling and Disposal Guides), Print Drivers and Warranty Statement  Installation Guide  Quick Use Guides  Power cord, USB Cable  Fax cord		
Supplies and Accessories	Quantity	Part Number	
Supplies			
Extra-High Capacity Print Cartridges	15,000 standard pages <sup>8</sup>	106R03623	
High Capacity Print Cartridges	8,500 standard pages <sup>8</sup>	106R03621	
Standard Capacity Print Cartridges	3,000 standard pages <sup>8</sup>	106R03773	
Drum Cartridge	30,000 standard pages <sup>9</sup>	101R00555	
Accessories			
550-sheet Paper Tray		097N02254	
Near Field Communication (NFC) Enablement Kit		097N02255	
WorkCentre 3335/3345 Card Reader Enablement Kit (without card reader) 497K17990		497K17990	

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

 $Return \, spent \, imaging \, supplies \, through \, the \, Xerox \, Green \, World \, Alliance \, collection/reuse/recycling \, programme.$ For more information, visit www.xerox.com/about-xerox/recycling.



<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput.
<sup>3</sup> Paper capacities are based on 20 lb. / 75 qsm stock; capacities will vary with different weight stocks.

<sup>&</sup>lt;sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

Frinting from USB.
Depending on the specific mobile device, versions or vendor, the mobile device may require a free download of the app from the appropriate store(s).

Requires analogue phone line.
Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>9</sup> Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.